

AC/DC Digital Clamp Meters

KEW

2003A

- Equipped to measure both AC and DC current with transformer jaws of large diameter.
- Can measure AC and DC currents up to 2000A.
- Output terminal for connection to recorders.

Φ55	MAX AC/DC 2000A	AC V	DC V
Ω	Continuity	OUT PUT	MAX HOLD



CE

AC A	400A/2000A (0~1000A) ±1.5%rdg±2dgt [50/60Hz] ±3%rdg±4dgt [40~500Hz] ±5%rdg±4dgt [500Hz~1kHz] 2000A (1001~2000A) ±3%rdg±2dgt [50/60Hz]
AC V	400/750V ±1.5%rdg±2dgt [50/60Hz] ±1.5%rdg±4dgt [40Hz~1kHz]
DC A	400/2000A ±1.5%rdg±2dgt
DC V	400/1000V ±1%rdg±2dgt
Ω	400/4000Ω ±1.5%rdg±2dgt
Continuity buzzer	buzzer sounds below 50±35Ω
Output	Recorder : DC400mV against AC/DC400A DC200mV against AC/DC2000A
Conductor Size	Ø55mm max.
Safety Standard	IEC 61010-1 CAT.IV 600V CAT.III 1000V IEC 61010-031 IEC 61010-2-032
Frequency Response	40Hz~1kHz
Withstand Voltage	6880V AC for 5 seconds
Power Source	R6P (AA) (1.5V) ×2
Dimensions	250(L) × 105(W) × 49(D)mm
Weight	530g approx.
Accessories	7107 (Test Leads) 8201 (Output Plug) 9094 (Carrying Case) R6P (AA) × 2 Instruction Manual
Optional	8008 (Multi-Tran) (AC only) 7014 (Output Cord)