

General Information

- 3-3/4 digits 4000 count
- Auto power off (Enable or Disable)
- Relative Function
- Body cover can also be used as a stand



Standard Accessories Included

- Strap x 1

General Specification



Function	Measuring range	Best accuracy	Resolution	Input impedance
DCV	400m/4/40/400/600V	±(0.7%+3)	0.1mV	10M~100MΩ
ACV	4/40/400/600V	±(1.6%+9)	0.001V	
DCA	40m/400mA	±(2.2%+5)	0.01mA	
ACA	40m/400mA	±(2.8%+5)	0.01mA	
Resistance	400/4k/40k/400k/4M/40MΩ	±(1.5%+5)	0.1Ω	
Capacitance	50n/500n/5μ/50μ/100μF	±(5%+10)	0.01nF	
Frequency	5Hz~100kHz	±(0.5%+3)		
Duty cycle	20%~80%	±(0.5%+5)		
Continuity	Buzzer sounds at between 10Ω and 120Ω. Open voltage : approx. 0.4V			
Diode test	Open voltage : approx. 1.5V			
Bandwidth	40~400Hz			
Fuse / Battery	0.5A/250V 1.5kA φ5.2X20 ceramic	R6PX2		
Size / Weight	H176XW104XD46mm/approx. 340g			
Standard accessories included	Hand strap , Instruction manual			