

Dual laser targeting, + type K thermometer

1,000 °C INFRARED THERMOMETER

Model : TM-969

ISO-9001, CE, IEC1010



Lutron

LUTRON ELECTRONIC

The Art of Measurement

Dual laser targeting, + type K thermometer

1,000 °C INFRARED THERMOMETER

Model : TM-969

FEATURES	
* None contact infrared temperature measurement up to 1,000 °C measurement.	
* Type K thermocouple thermometer, up to 1400 °C measurement.	
* Dual laser for better targeting.	
* Large LCD display with back light.	
* D/S ratio value : 50/1.	
* Min., Max., Differential, Average, Lock mode.	
* Last measurement memory.	
* Hi/Lo Temperature Audio Alarm.	
* Laser target and Back light On/Off control.	
* Adjustable emissivity value from 0.1 to 1.00.	
* Preset emissivity value at 0.95.	
* Power supply by two AAA batteries, long life.	

GENERAL SPECIFICATIONS				
Display	LCD, 31 mm x 43 mm.		Measurement	8 to 14 micro meter.
Functions	* °C, °F.		Wave length	Region
	* Min., Max., Differential, Average.		Distance Factor	
IR Measurement Range	* Lock mode.			* <i>Distance to spot using 90% encircled energy at focal point.</i>
	* Auto power off.			
IR Accuracy	* LCD back light.		Target Guide	* Two laser target guide. * Less than 1 mW. * Class 2 red laser diode. Wave length is 645 nm approximately.
	* Emissivity adjustment.			
Type K Thermometer Range	-60 to 1000 °C (-76 to 1832 °F).		Sampling Time	Approx. 0.7 second.
	± 1 °C (1.8 °F) * <i>Object Temp. = 15 to 35 °C</i> * <i>Ambient Temp. = 25 °C</i>			
Type K Thermometer Accuracy	± 2 % of reading or ± 2 °C (± 4 °F). whichever is greater.		Power Supply	DC 1.5V AAA (UM-4) battery x 2 PCs, heavy duty or Alkaline.
	* <i>Object Temp. = -33 to 1000 °C</i> * <i>Ambient Temp. = 23 ± 3°C</i>			
Type K Thermometer Range	-64 to 1400 °C (-83.2 to 1999 °F).		Power Consumption	without target light on : <i>Approx. DC 1.5 mA.</i>
				with target light on : <i>Approx. DC 29.5 mA.</i>
Type K Thermometer Accuracy	± 1 % of reading or ± 1 °C (± 1.8 °F), * Test under T ambient = 23 ± 5 °C		Operating Temperature	0 to 50 °C (32 to 122 °F).
	Resolution	0.1 °C / 0.1 °F.	Operating Humidity	Less than 80% RH.
1 °C / 1 °F.		Weight		
Circuit	Exclusive microcomputer circuit.		Dimension	203 x 197 x 47 mm (8.0 x 7.7 x 1.8 inch)
Emissivity Adjustment	Adjustment range : 0.10 to 1.00, step 0.01. * 0.95 default emissivity value.		Standard Accessories	Operational manual..... 1 PC.
IR Temp. Sensor	Thermocouple pie.			Magnetic stand..... 1 PC.
				Hard carrying case..... 1 PC.
				DC 1.5V AAA (UM-4) battery..... 2 PC.

* Appearance and specifications listed in this brochure are subject to change without notice.

0709-TM969