

TES-1336A Datalogging Light Meter (RS-232)



FEATURES

- Spectrum of photo sensor meets C.I.E. photopic curve V(λ)
- 16000 Records Data logging capacity
- RS-232 interface (software included)
- Measurement of luminous intensity (PC Software)



SPECIFICATION

Measuring range	20/200/2000/20000 Lux, 20/200/2000/20000 Fc
Luminous intensity (cd)	Intensity = illuminance x (length) ²
Length	feet (Fc) meter (Lux)
Resolution	0.01 Lux
Accuracy	±(3% rdg + 5dgts) (calibrated to standard incandescent lamp, 2856 K)
Overrange display	OL
Record (Data logging)	16000 Point Data logger
Sensor	Silicon photo diode
Sensor lead length	150cm (approx)
Sensor probe	100(L) x 60(W) x 27(H) mm
Power source	One 9V battery
Battery life	50hrs (approx)
Operating Storage Condition	0 °C ~ 40 °C (32 °F~104 °F) below 80% RH -10 °C ~ 60 °C (14 °F~140 °F) below 70% RH
Dimensions	146(L) x 70(W) x 39(H) mm
Weight	300g (approx)
Accessories	Carrying case、 9V battery、 instruction manual、 Software、 RS-

232 cable、 9 Pin to 25 Pin gender
changer screwdriver.