

## Testo 606 - Material moisture, air temperature and humidity



- Available in two models:
  - Testo 606-1** material moisture
  - Testo 606-2** material moisture, air temperature and humidity
- Measurement of wood moisture e.g. beech, spruce, larch, oak, pine and maple
- Air temperature and humidity for monitoring drying processes
- Curves for cement screed, concrete, plaster, anhydrite, cement mortar, lime and brick
- Hold and auto-test functions

### Technical data

#### Material moisture

Measuring range: 0 to 90%

Resolution: 0.1

Accuracy:  $\pm 1\%$  (conductivity)

#### Air humidity (606-2 only):

Measuring range: 0 to 100%rh

Resolution: 0.1%rh

Accuracy:  $\pm 2.5\%$ rh (5 to 95%rh)

Units: %rh, wet bulb, dewpoint

#### Air temperature (606-2 only)

Measuring range: -10 to 50°C

Resolution: 0.1°C

Accuracy:  $\pm 0.5\ ^\circ C$

Units: °C/F

Oper. temp.: -10 to 50 °C

Battery type: Alkaline (2 x AAA)

Battery life: 606-1: 200 h.

606-2: 130 h.

(average, without display illumination)

#### Dimensions

(incl. protective cap): 119 x 46 x 25 mm

#### Included in delivery:

Calibration protocol · Wrist strap

Belt holder · Protective cap · Batteries

606-1: Part no. 0560 6060

606-2: Part no. 0560 6062