

CM-01 DC/AC Clamp Meter



FEATURES

High Resolution DC/AC 10mA
23 mm Large Jaw Diameter
One Touch Zero for DCA adjustment



SPECIFICATION

Range	Resolution	Accuracy	Remarks
DCA 0-40A	10mA	+/- 1.0% +/- 2dgts	
DCA 0-150A	100mA	+/- 1.0% +/-2 dgts	
DCA 150-200A	100mA	-2.2% +/- 2dgts	
ACA 0-40A	10mA	+/- 1.0% +/- 3 dgts	
ACA 0-150A	100mA	+/- 1.0% +/- 3 dgts	
ACA 150-200A	100mA	-2.2% +/- 3dgts	
DCV 0-400V	0.1 V	+/- 1.0% +/- 2dgts	
ACV 0-400V	0.1 V	+/- 1.0% +/- 2 dgts	
W 0-400 W	0.1 W	+/- 1.0% +/-2dgts	beep if < 40 W (Approx.)
Hz 0-1000KHz	0.1-100	+/- 0.5% +/- 2dgts	1V sensitivity Auto Range

Power Source: 2 X 1.5V AA UM3 Batteries

Current Consumption: 10mA

Operating Condition: -10 °C to 50 °C at 85% max. RH