

CM-03 Leakage Current Tester



FEATURES

10 m A Ultra High Resolution
Large Conductor Diameter (30mm)
ACA 5 Ranges (40mA, 400mA, 4A, 40A, 100A)



SPECIFICATION

Range	Resolution	Accuracy	
		50/60Hz	Wide
ACA 0-40mA	10 m A	+/- 1.5% rdg +/- 3 dgts	+/- 2.0% rdg +/- 5 dgts (40 to 1KHz)
ACA 0 -400mA	100 m A	+/- 1.5% rdg +/- 3 dgts	+/- 2.0% rdg +/- 5 dgts (40 to 1KHz)
ACA 0-4A	1mA	+/- 1.5% rdg +/- 3 dgts	+/- 2.0% rdg +/- 5 dgts (40 to 1KHz)
ACA 0-40A	10mA	+/- 1.5% rdg +/- 3 dgts	+/- 2.0% rdg +/- 5 dgts (40 to 1KHz)
ACA 0-80A	0.1A	+/- 2.2% rdg +/- 5 dgts	+/- 2.5% rdg +/- 5 dgts (40 to 1KHz)
ACA 0-100A	0.1A	+/- 5.0% rdg +/- 5 dgts	+/- 2.5% rdg +/- 5 dgts (40 to 1KHz)
ACV 0-400V	0.1V	+/- 1.0% rdg +/- 3 dgts	+/- 2.0% rdg +/- 4 dgts (40 to 1KHz)
W 0-400 Ohm	0.1 Ohm	+/- 1.0% rdg +/- 3 dgts	Beef if < 40 W

Power Source:
2 X 1.5V SUM-3 Batteries

Operation Temperature/Humidity:
-10 °C to 50 °C at 85% max.