

**Name:**

Basic Tone and Probe Kit

Cat #:

601K-G

UPC #:

49989

Spec:**Probe Specifications**

Gain (nominal): 30 db
Input Impedance (nominal): 100 M Ω
Plastic tip resistance: 300 Ω
Battery: 9 VDC (NEDA 1604, JIS 006P, or IEC 6LR61)
Battery Life (Nominal): >50 hours
Length: 231 mm (9.0")
Width: 55mm (2.2")
Depth: 28 mm (1.1")
Weight: 145 g (5.2oz)
Operating/Storage Temperature: 0° C to 50° C (32° F to 122° F)

Generator Specifications

Talk Battery (into 600 Ω): 4.6VDC
Output Power (into 600 Ω): + 10dBm
Resistive Short Visual Indication: <10k Ω
Output Frequency: Alternating-890/960 Hz, Warbling-Slow 1.3 Hz/Fast: 6Hz
Voltage Protection (into 600 Ω): 52 VDC
Battery: 9 VDC (NEDA 1604, JIS 006P, or IEC 6LR61)
Battery Life: >50 hours
Height: 57 mm (2.25")
Width: 64 mm (2.5")
Depth: 32 mm (1.25")
Weight (max): 128g (4.5 oz.)
Operating Temperature: 0° C to 50° C (32° F to 122° F)
Storage Temperature: -50° C to 75° C (-58° F to 167° F)

Description:**Benefits**

- Ease of operation
- Reliability
- Large speaker for noisy environments.

Probe

- Adjustable volume control
- Replaceable tip

Tone Generator

- Continuity & Polarity LED
- External warble select
- Short Circuit LED
- Single line modular LED
- Alligator Connector Clips