

NETcat® Pro NC-500 Structured Wiring Troubleshooter



One Touch Testing Verifies Network Cabling and Service.

The NETcat® Pro is a digital tool for fast, accurate checking of cables, wiring and network service. Operated using a back-lit touch screen display, the Pro not only tests wiring continuity and proper pair allocation, but measures the length of cables and determines if network service is available. When used with the NC-510 Accessory Kit containing seven (7) expansion remote test

modules, the NETcat Pro can uniquely test coax or twisted pair jacks from a central location eight (8) at a time. Using either a fingertip or the built-in stylus, the screen can be used to control and display a range of tests from fault finding to TDR length measurement. The display can be set to English, Spanish or French language.

PRODUCT FEATURES

- Touch screen display with contrast adjustment and backlight.
- Tests shielded twisted pair (STP) unshielded twisted pair (UTP) and coaxial cables.
- 0-2000 foot cable length via TDR.
- Generate four distinct, precision tones for tracing low-loss cables like Cat 5.
- Identifies active network devices (PC or Hub) on 10/100 Base-T networks.
- Displays network device capabilities.
- Patch cable and remote jack wire-map.
- Detects shorts, opens, reversed, crossed and split pairs.
- Office identification using remote ID units.
- Troubleshoots and verifies a wide range of networks.
- Graphical touch-screen display.
- Remote jack ID and verification.
- Operates on a single 9V battery, with low battery indicator.
- Pulsed time domain reflectometer (TDR) shows length of all pairs.
- Compatible with Greenlee precision digital probes.

SPECIFICATIONS

Dimensions:	3.3" x 1.4" x 6.7" (8.5 cm x 3.5 cm x 17 cm)	Interface Connections:	RJ45 shielded jacks F-type threaded female coaxial connectors
Weight:	0.45 lb. (200 g)	TDR Calibration:	User selectable based on a known cable length. Range: 50 to 2000 ft. - 40% to 100% in step of 1%
Power Requirements:	9V Alkaline battery (PP3)	Length:	2000 ft Maximum
User Interface		Resolution:	1 ft.
Display LCD:	Dot Pixels: 128 x 128 dots	Accuracy to Open/Short:	+4% or 2 ft. whichever is greater
Viewing area:	60.0 x 58.4	Remote Identifier:	2000 ft. (609.6 meters) maximum distance
Backlight:	White LED	Wiremap:	358 ft (100 meters) maximum distance
Buttons:	LCD touch-screen, Single momentary contact push button		
Environmental			
Operating Temperature:	0°C to 50°C		
Storage Temperature:	-20°C to 70°C		

ORDERING INFORMATION

CAT NO.	UPC NO.	DESCRIPTION	QTY
NC-500	23639	NETcat Pro Digital VDV Wiring Troubleshooter	1
NC-510	23640	NETcat Pro Accessory Kit w/carry case and eight (8) digital remote units	1

DISTRIBUTED BY:



USA: 800-435-0786 Fax: 800-451-2632
815-397-7070 Fax: 815-397-1865
Canada: 800-435-0786 Fax: 800-524-2853
International: +1-815-397-7070 Fax: +1-815-397-9247
4455 Boeing Drive • Rockford, IL 61109-2988 • USA • 815-397-7070
©2006 Greenlee Textron Inc. • An ISO 9001 Company • Printed in USA
Greenlee Textron Inc. is a subsidiary of Textron Inc.
www.greenlee.com MA-4824 5/06