

Wireless Inspection Camera With Recordable Monitor



Model No.: 8803AL

FEATURES

- Allows for easy surveying of small, hard-to-reach places
- Mini 9mm water-proof camera with 1m (3 ft.) flexible extended tube
- Manufactured and tested to IP67 waterproof standard
- 3.5" TFT-LCD detachable/mountable monitor, built-in rechargeable Li-battery
- Video recording capability, supports up to 32GB micro SD card
- Adjustable brightness on lens-mounted LED light
- 3 useful accessories included: Hook, mirror and magnet
- Lightweight, handheld design, flexible and convenient to use

SPECIFICATIONS

	Items	Specifications
CAMERA	Imaging sensor	CMOS
	Total pixels	640×480
	View angle	45°
	Transmission frequency	2468MHz
	Minimum illumination	0 Lux
	Modulation type	FM
	Bandwidth	18MHz
	Power supply	4×AA batteries
	Unobstructed effective range	10m
	Waterproof capacity	IP67 (Only for imager head)
	Dimensions (W×D×H)	186×145×41(mm)(Exclude flexible tube)
	Weight (about)	450g
	RECEIVER	LCD screen type
Effective pixels		960×240
Video system		PAL/NTSC
Transmission frequency		2414MHz,2432MHz,2450MHz,2468MHz
Exterior supply voltage		5V _{DC}
Consumption current		500mA (Max.)
Charge time		3 hours
Work time		2 hours
Picture/Video pixels		640×480
Video size		27M byte/minute
Frame rate		30 frame/second
Video output level		0.9-1.3V _{RMS} @75ohm
Receiving sensitivity		≤-85dBm
Dimensions (W×D×H)	100×70×25 (mm)	
Weight (about)	140g	
Operating temperature	-10°C~50°C/14°F~122°F	
Operating humidity	15%~85%RH	